Buz® Ovenmaster G 574

High alkaline combi oven and steam cleaner





HACCP COMPLIANT

SILICONE-FREE

PERFUME-FREE

DYE-FREE

Area of application

- In the food processing sector including bakeries, butchers and large kitchens in the catering and hotel industry etc.
- For convection ovens (hot air ovens), combination steamers, grills and ovens, deep fryers, tilting frying pans, extractor hoods, grease filters and smoke chambers
- Also for pans, pots, trays and other heavily soiled work equipment
- Alkali-resistant surfaces such as stainless steel, glass, tiles, plastic, porcelain

Product properties

- Self-acting and foaming grease crust breaker and smoke resin remover
- For manual cleaning and for cleaning with an automatic cleaning system
- Universally applicable
- Good grease-removing properties
- Excellent removal of burnt-in dirt, grease and protein residues, oils and incrustations
- No odor, chlorine and phosphate free
- Can be rinsed easily and without leaving any residue

Application and dosage

- Can be used on cold and warm surfaces (>50°C).
- The information provided by the device manufacturer must be taken into account when cleaning.


100 - 1.000 ml / 10 l water


1:5 - 1:10 with water

- Apply fresh application solutions and consume them within 24 hours at the latest.

Note


- Not suitable for alkali-sensitive materials such as aluminium or non-ferrous metal.
- Surfaces or objects that come into direct contact with food must be cleaned of cleaning residues by careful rinsing with water.
- Do not mix with other cleaners.
- Before changing the product, rinse the dosing system including the suction hoses with water.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

- **Product colour:** colourless
- **GISBAU code:** GG 70
- **UFI code:** UEW0-Q090-3002-SQYR
- For professional use only.

Sales units

- G574-0010RA: 1 x 10 l canister



Date 29.10.2024

Remark: Some products may not be available in all territories. Please talk to your customer service representative.
The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

BUZIL-WERK Wagner GmbH & Co. KG • Fraunhoferstraße 17 • D-87700 Memmingen • www.buzil.com