Frost Clean
G 579

Deep freezer cleaner up to -30°C





HACCP COMPLIANT
SILICONE-FREE
PERFUME-FREE
DYE-FREE

Area of application

- For cooling and freezing systems in the food processing industry during ongoing operation
- For all water and alcohol resistant floors, walls, surfaces and objects
- Can be used on ceramic tiles, tiles, porcelain stoneware and safety tiles, aluminum, stainless steel, chrome as well as industrial flooring such as screed and concrete

Product properties

- Excellent cleaning power even at low temperatures
- Removes general and pigmented dirt, especially stubborn oily and greasy dirt
- Effective wetting effect without disruptive foaming
- Quick drying to create non-slip surfaces
- Has a de-icing effect and enables cleaning during operation without defrosting, without storage and without interrupting the cold chain
- Material-compatible
- Can be used immediately as it is ready to use
- Can be used mechanically and manually

Application and dosage



undi-
luted

- Manual surface cleaning: For vertical surfaces, the product can be sprayed on or applied with a microfiber cloth or table mop. After application, work the product into the surface using a hard brush. Then pick up the loosened dirt with an absorbent cloth.
- Application with scrubber dryer: Scrub the floor covering with a single-disc machine or automatic scrubber dryer and a suitable pad or a nylon scrub brush. Then vacuum up the dirt solution.

Note

- When used on plastics and acrylic glass (PMMA), a material compatibility test is recommended.
- All unpackaged food must be removed before cleaning.
- Do not dilute the product with water for use in the freezer compartment.
- Ensure there is sufficient supply of fresh air during processing.
- Store in a cool and dry place.
- Avoid direct sunlight.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

- **Product colour:** colourless
- **UFI code:** 2HW0-60YD-D00K-F2JT
- For professional use only.

Sales units

- G579-0010RA: 1 x 10 l canister

pH 9,5
0 2 4 6 8 10 12 14

Date 29.10.2024

Remark: Some products may not be available in all territories. Please talk to your customer service representative.
The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

BUZIL-WERK Wagner GmbH & Co. KG • Fraunhoferstraße 17 • D-87700 Memmingen • www.buzil.com